



รับประกันคุณภาพ
๑-โหล่แท้และบริกรม

องค์กรแห่งแรกของไทย



ที่ได้มีมาตรฐานคุณภาพสินค้าและบริการด้านวิศวกรรม
ISO 9001 : 2015

160^{CH}
New!
BAND PLAN
200 - 340 MHz

2 YEARS
WARRANTY

GET IT NOW!!

SUPER HOT

จ๊ว แต จ๊ว

ขนาดเล็ก | ยกเว้นใบอนุญาตพกพา



SPECIFICATIONS

- 160 CHANNELS, 40 FREE MEMORIES
- 214 CODES OF DCS
- 51 GROUPS OF CTCSS
- BABY MONITOR (BBM)
- ROGER BEEP SOUND (ROGER)
- BATTERY SAVER
- PTT ID (TYPE OF PTT ID)
- BUSY CHANNEL LOCK OUT
- TIME-OUT TIMER (TOT)



BABY MONITOR



BATTERY SAVER



BATTERY 1100 mAh.



214 CODES OF DCS



TIME - OUT TIMER

SPECIFICATION ID2462

GENERAL

| | |
|-----------------------------|--------------------------------|
| FREQUENCY COVER RANGE | 245.0000 - 246.9875 MHz. |
| CHANNEL | 160 Channels, 39 Free Memories |
| CHANNEL SPACING | 12.5 KHz. |
| OPERATION TEMPERATURE RANCE | -20 °C ~ +50 °C |
| FREQUENCY STABILITY | ± 5 ppm (-20 °C ~ +50 °C) |
| POWER SUPPLY REQUIERMENT | 3.7V DC. |
| CURRENT STAND-BY | 20mA. |
| DIMENSIONS | 96 x 58 x 32 (H x Wx D) |
| WEIGHT | 95g. (with battery) |
| COLOR | Red |



BATTERY 1100 mAh.



USB



ADAPTOR



ANTENNA

TRANSMITTER

| | |
|--------------------------|------------------------|
| OUTPUT POWER | Hi : 0.5w./ Lo : 0.1w. |
| SUPRIOUS RADIATION | 63dB. |
| ADJACENT CHANNEL POWER | < -63dBm. |
| MAX. FREQUENCY DEVIATION | ± 2.5 KHz. |
| TX DISTORTION | < 5% |



SMALL TALK



BELF CLIP

RECEIVER

| | |
|---------------------|---------------------------|
| SENSITIVITY | < 0.25µV. at 12dB./ SINAD |
| SQUELCH SENSITIVITY | < 0.158µV. |
| SELECTIVITY | - 65dBm. |
| INTERMODULATION | 65dB. |
| AUDIO OUTPUT MAX | > 500 mW. |
| AUDIO DISTORTION | < 5% at 8 Ohm Speaker |



HAND STRAP



USER'S MANUAL