










CB-22

High Performance
Citizen Band Radio

- ความสะดวกสบาย
- สแตนด์บาย 2 ช่องสัญญาณ
- ช่องเสียบชาร์จ USB-C
- แบตเตอรี่ความจุสูง 2,000 mAh
- มาตรฐาน IP54 และ MIL-STD-810G
- ดีไซน์เล็กบาง กั้นสมัย

Features

-  Escalating Alarm
-  Voice Prompt
-  6 Steps Frequency
-  Transmission Timeout Limit
-  Programmable Keypads
-  50 CTCSS & 104 DCS
-  Power Saving Mode
-  VOX Sound-Control
-  CE Standard
-  Tail Cancellation

Special Function

- Ultimate Compact Design (108 X 52 X 28 mm)
- Large LCD Display Allowing Outdoor Strong light, Features a larger pixel aperture color display with a flexible menu-driven interface
- 5 Watts Of Reliable RF Power within An Ultra-Compact Body
- Set Up Name Replace Channel
- Memory Display Mode / Channel Display Mode
- Password Security Set Up
- Three Selectable TX Power Settings: 5W High / 2W Middle / 0.5W Low
- One Watt Powerful Audio Output And Clear Audio From The 36mm Front Speaker
- QRK (Quick Recall Keys) Two User Programmable Keys For Direct Access To Favorite Functions
- 199 Memory Channels
- Beep Sound On/Off
- Roger Beep Sound
- Channel Announcement
- Over 15 Hours Operating Time with Supplied 2000mAh Li-Ion Battery Pack
- Micro-USB Rapid Charger (TBL-17 with TPC-06 & TCA05)
- Versatile Scanning Capabilities: VFO Scan, Memory Scan, Programmable Memory Scan(PMS), Memory Bank Scan, And Dual Receive
- VOX Operation with Optional VOX Earpiece Microphone
- PC Programmable with Optional Programming Cable
- Transceiver-To-Transceiver Cloning with Optional Cloning Cable
- FM Broadcast Receiver Equipped
- 8 DTMF Autodial Memories
- CTCSS / DCS Operation
- Busy Channel Lock Out (BCLO)
- Battery Saver Function
- Transmitter Time Out Timer (TOT)
- BIIS PTT ID And Emergency Call
- Surveillance Function



PRODUCT DESCRIPTIONS



PRODUCT ACCESSORIES

Standard Accessories



Optional Accessories



PRODUCT SPECIFICATIONS



General Specifications

Model Number	CB-22
Frequency Range	245.000–246.9875 MHz
Power	5W/1W
Number of channels	400
Communication standard	Analogue
Frequency Stability	±2.5ppm
SOS Alarm	1
Weight	210g/7.58oz
Dimensions	108x52x28(mm) / 4.25x2.04x1.1(in)
Programmable Keys	2
Antenna Type	245.000–246.9875 Antenna
Antenna impedance	50Ω
Battery Capacity	Standard 2000mAh, 7.4V
Battery Life	2000mAh Battery: Stand by: 48hrs; Talk (5–5–90): 8hrs 3000mAh Battery: Stand by: 84hrs; Talk (5–5–90): 12hrs

Receiving Part

Receiving sensitivity	<0.20uv(12dB SINAD)
Squelch sensitivity	<0.2uV
Intermodulation anti-interference	65dB
Audio distortion	<5%
Audio power	1W
Receive current	≤380mA
Audio response	+1~–3dB
Clutter resistance	≥65dB

Certification

CE FCC & IC ID	CE
Dustproof and waterproof	IP54 standard

The above specifications are tested according to applicable standards. Due to the continuous development of technology, the above data is subject to change without notice.

Launch Part

Emission current	≤1.3A
Maximum deviation frequency	≤5KHz/≤2.5KHz
Stray power	≤ 7.5uW
Adjacent channel power	≤–65dB

Launch Part

QT/DQT Frequency deviation	0.7± 0.1KHz/0.4±0.1KHz
Signal-to-noise ratio	≥–45dB/≥–40dB
Modulation sensitivity	8–12mV
Output Power	5W/1W

Environmental Index

MIL-STD	810C	810D	810E	810F	810G
Low Pressure	500.1/ I	500.2/ I, II	500.3/ I, II	500.4/ I, II	500.5/ I, II
High Temperature	501.1/ I, II	501.2/ I, II	501.3/ I, II	501.4/ I, II	501.5/ I, II
Low Temperature	502.1/ I	502.2/ I, II	502.3/ I, II	502.4/ I, II	502.5/ I, II
Temperature Shock	503.1/ I	503.2/ I	503.3/ I	503.4/ I, II	503.5/ I, II
Solar Radiation	505.1/ I	505.2/ I	505.3/ I	505.4/ I	505.5/ I
Rain	506.1/ I, II	506.2/ I, II	506.3/ I, II	506.4/ I, III	506.5/ I, III
Humidity	507.1/ I, II	507.2/ II, III	507.3/ II, III	507.4	507.5/ II
Salt Fog	509.1/ I	509.2/ I	509.3/ I	509.4	509.5
Dust	510.1/ I	510.2/ I	510.3/ I	510.4/ I, III	510.5/ I
Vibration	514.2/ VIII, X	514.3/ I	514.4/ I	514.5/ I	514.6/ I
Shock	516.2/ I, II, V	516.3/ I, IV	516.4/ I, IV	516.5/ I, IV	516.6/ I, IV

DEALER

จัดจำหน่ายโดย

บริษัท นิว เวฟ ดิจิตอล จำกัด

4/26 ถนนคลองลำเจียก แขวงบวรจันทร์ เขตบึงกุ่ม กรุงเทพฯ 10230

Tel: 02-509-1983-4, Web: nwd.co.th, Facebook: NWD วิทยุสื่อสาร