

**VX-1R**

**ตอบสนองความต้องการ ทนทานสุด  
"สุดคุ้มด้วยราคาเบาๆ"**

**HIMAX**

**ISO-9000  
ISO-14001**



**CE**



**VX-1R**

Receiver	
Frequency Range	245.000-245.9875 MHz
Sensitivity	≤0.2μV
Occupied bandwidth	< 11 KHz
Adjacent channel selectivity	≥65dB
Intermodulation	≥55dB
Audio output power	> 500m W
Audio distortion	≤10%
Frequency Stability	5ppm
Current	standby 60mA working<160mA
Audio response (300-3400Hz)	+1~-3dB
Transmitter	
Frequency Range	245.000-245.9875 MHz
RF power	0.5 W
Modulation Type	FM
Spurious power	≤7.5μW
Modulated noise	<-40dB
Intermediation distortion	<5%
Frequency Stability	5ppm
Maximum deviation	+/- 2.5Khz
Current	≤1250mA
Audio response (300-3400Hz)	+1~-3dB
Adjacent channel power	≥65dB



เหมาะกะบ

- Tourism : กรุ๊ปทัวร์, แรลลี่, จักรยานแรลลี่, ท่องเที่ยว
- Entertainment : โรงแรม, ร้านอาหาร, สปา
- Outdoor : เข้าค่ายโรงเรียน, มหาวิทยาลัย

อุปกรณ์มาตรฐาน



อุปกรณ์พิเศษ

