



VX-417/427 Series

Under Easy-Licenses Band

SPECIFICATION SHEET

Dependable and Discreet Communications

The Vertex Standard VX-417/427 Series provides a host of built-in features in compact convenience for the quality communications you need.

Large Channel Capacity for Group Communications

For large group communications, Or get 32-channel capacity, with the VX-417/427 radios for quick and convenient channel access.

Maximise Battery Life

Includes RX/TX (receive and transmit) battery saver capability. During receive, the radio will go into saver mode while periodically checking for channel activity. During transmit, the VX-417/427 Series will automatically reduce power when the incoming signal is very strong.

Exclusive Auto-Range Transpond System – ARTS™

Only Vertex Standard radios are designed to inform you when you and another ARTS™-equipped station are within communication range. If out of range for more than 2 minutes, your radio senses no signal has been received and beeps to alert you. The base station can then alert the field unit to move back in range. A great solution to keep your workers co-ordinated.



The Vertex Standard Difference

Our number one goal is achieving superior customer satisfaction by delivering products and services that exceed your expectations. Count on Vertex Standard for radios that are built to last and designed to provide more features for a better return on your investment. Ask your Dealer for more details.



VX-417/427 Series



SPECIFICATION SHEET

vertexstandard.com

Additional Features

- Six programmable key (VX427)
- Two programmable key (VX417)
- 8-Character alphanumeric display (VX427)
- DTMF ANI
- 2-Ton Encode + Dual 2-Tone Decode
- CTCSS / DCS Encode & Decode
- 5-Tone signaling
- Compander
- BCLO, BTLO and TOT Functions
- Programmable alert tone

VX-417/427 Series Specifications

General Specification		VX 417 / 427
Frequency Range	(350-351MHz)	
Number of Channels	32 ch	
Power Supply Voltage	7.5V DC \pm 20 %	
Channel Spacing	12.5kHz	
PLL Steps	2.5 / 6.25 kHz	
Battery Life (5-5-90 duty)	1800 mAh , Ni -MH Battery model FNB-V 94	
IP Rating	IP 54	
Operating Temperature Range	-30° C to +60° C	
Frequency Stability	\pm 2.5 ppm	
Dimension (H x W x D)	(108.5 x 58 x 30 mm)	
Weight (Approx.)	(300 g , ANT, Belt Clip)	
Receiver Specification: measured by TIA/EIA-603		
Circuit Type	Double-conversion Super-heterodyne	
IFs	50.85MHz & 450 kHz	
Sensitivity 12 dB SINAD	0.25 μ V	
Squelch Sensitivity	< 0.20 μ V	
Adjacent Channel Selectivity	> 70 dB (25/20 kHz) / > 65 dB (12.5 kHz)	
Intermodulation	> 70 dB	
Spurious and Image Rejection	> 70 dB	
Audio Output	500mW@ 4 Ohms 5% THD	
Transmitter Specification: measured by TIA/EIA-603		
Output Power	4 / 1 W	
Modulation	11K0F3E	
Conducted Spurious Emissions	70 dB below carrier	
FM Hum & Noise	> 45 dB	
Audio Distortion	< 3% @1 kHz	
Microphone Type	2-kOhms condenser	

Applicable MIL-STD

Standard	MIL 810D Methods/ Procedures	MIL 810E Methods/ Procedures	MIL 810F Methods/ Procedures
Low Pressure	500.2/Procedure I, II	500.3/Procedure I, II	500.4/Procedure I, II
High Temperature	501.2/Procedure I, II	501.3/Procedure I, II	501.4/Procedure I, II
Low Temperature	502.2/Procedure I	502.3/Procedure I, II	502.4/Procedure I, II
Temperature Shock	505.2/Procedure I	505.3/Procedure I	505.4/Procedure I, II
Rain	506.2/Procedure I, II	506.3/Procedure I, II	506.4/Procedure I, III
Humidity	507.2/Procedure II, III	507.3/Procedure II, III	507.4/Procedure I
Salt Fog	509.2/Procedure	509.3/Procedure I	509.4 /Procedure I
Dust	510.2/Procedure I	510.3/Procedure I	510.4/Procedure I
Vibration	514.3/Procedure Cat. 10	514.4/Procedure Cat. 10	514.5/Procedure Cat. 10
Shock	516.3/Procedure I, V	516.4/Procedure I, IV	516.5/Procedure I, IV

Specifications are subject to change without notice or obligation.

VERTEX STANDARD is registered in the US Patent & Trademark Office. All other product or service names are the property of their respective owners. © Vertex Standard Co. Ltd. 2010